







Cylindrical, straight galvanised steel lighting poles



- Pre-treated and coated by the high-quality, UV-resistant, powder coating for ensuring high corrosion resistance
- Material: Galvanised steel
- Form: Cylindrical, straight
- Installing options: Mounting base or anchor bolts on a foundation
- Manufacturing process is in accordance with EN40 standard
- Height options: 2 m, 2.5 m, 3 m, 3.5 m, 4 m, 4.5 m, 5 m, 6 m, 7 m, 8 m
- Diameter/dimension options: Ø114 mm, Ø140 mm
- Spigot options: 60 mm, 76 mm

Height (mm)	Diameter / dimension (mm)	Thickness (mm)	Weight (kg)	Horizontal loads resistance (V ref,0 - m/s)	Luminaire weight (max - kg)	Luminaire wind catching area (max - m2)	EPA (m2)	Root mount kit	Circuit breaker box IP44	Technical Drawing
3000	Ø102	0	37.9	50	50	0.25	0.344	A20491	A21291	
3500	Ø102	0	43	45	50	0.25	0.401	A20491	A21291	
4000	Ø102	0	47.4	40	50	0.25	0.458	A20491	A21291	
4500	Ø102	0	51.1	32	50	0.25	0.515	A20491	A21291	
5000	Ø102	0	56.5	28	50	0.25	0.572	A20491	A21291	
6000	Ø102	0	65.9	22	50	0.25	0.686	A20491	A21291	
7000	Ø102	0	113.1	28	50	0.25	0.982	A23691	A21291	